


EASYIO FR RELAY MODULE.




FR-02 RELAY MODULE.



The FR-02 is a relay module which can be mounted on DIN rail. It allows 1 x AO coming from a controller to provide floating control via two built-in relays. Modes 1 or 2 are selected by a jumper on the FR-02. Relays rated for 5 million cycles.

THE DIMENSIONS.



THE SPECIFICATIONS.

DETAILS:

<i>Power Supply</i>	24Vac(+/-5%), 20VA or 24Vdc(+15%/-15%), 15VA, Class 2
---------------------	--

INPUTS & OUTPUTS:

<i>Analog input</i>	Voltage 0-10 Vdc, Class 2
<i>Digital outputs</i> (SPST N.O. dry contact)	24V AC/DC 2A (48VA)

THE SPECIFICATIONS.

MODE 1 (FLOATING MODE)

Stage	Min volt	Max volt	Optimum volt	DO 1 state	DO 2 state
1	0.00	1.00	0.00	OFF	OFF
2	1.10	5.00	3.00	ON	OFF
3	5.10	6.00	5.50	OFF	OFF
4	6.10	10.00	8.00	OFF	ON

MODE 2 (STAGING MODE)

Stage	Min volt	Max volt	Optimum volt	DO 1 state	DO 2 state
1	0.00	2.50	2.00	OFF	OFF
2	2.60	5.00	3.50	ON	OFF
3	5.10	7.50	6.50	OFF	ON
4	7.60	10.00	8.50	ON	ON

PARTNER DETAILS.

CONTACT

EasyIO Europe B.V.

info@easyio.eu www.easyio.eu

EasyIO Holdings Pte Ltd.

info@easyio.com www.easyio.com

All specifications subject to change without notice or liability to provide changes to prior purchasers, information and specifications published here are current as of the date of publication of this document. EasyIO reserves the right to change or modify specifications without prior notice. The latest product specifications can be found by contacting us.